


THOMAS ZIP 22



						kW	mt/min			OPTION 1PH kW 0.75 
		0°	45°	60°	2085x20x0,9	0.37/0.75	32/64	205 mm	165	
		180	120	50	 IMBALLO / PACKING	A= 680 mm B= 1400mm H= 1040 mm	 INGOMBRO / DIMENSIONS	A= 920 mm B= 1500 mm		
		180	110	50						
		200x150	120x110	50x70						

 Segatrice a nastro manuale ZIP 22 per il taglio di profili metallici e materiali pieni, ideale per carpenteria leggera e piccole produzioni in serie. Consente tagli da 0° a 60° a destra con battute di arresto e leva di bloccaggio per il fissaggio anche ad angolazioni intermedie. Il pulsante di avviamento della lama è integrato nell'impugnatura della leva arco, per un controllo immediato durante il taglio. La macchina è equipaggiata con motore trifase a due velocità di rotazione lama, disponibile anche in versione monofase a una velocità. Il tensionamento del nastro è meccanico tramite volantino, mentre la morsa manuale con bloccaggio rapido a leva e ganasce zigrinate in acciaio assicura un serraggio efficace anche nel taglio di tubi. Dotata di blocchetti guida lama con cuscinetti, elettropompa per la lubrificazione durante il taglio e spazzola pulilama per mantenere la lama pulita e prolungarne la durata. Il pannello comandi ergonomico consente un utilizzo semplice e immediato. Altezza piano di lavoro: 920 mm. Disponibile anche nella versione HB con discesa dell'arco gravitazionale*.

 Manual band saw ZIP 22 designed for cutting metal profiles and solid materials, ideal for light fabrication work and small batch production. It allows cuts from 0° to 60° to the right, with preset stops and a locking lever to secure the bow at any intermediate angle. The blade start button is integrated in the bow handle, allowing immediate control during cutting operations. The machine is equipped with a two-speed three-phase motor, also available in a single-phase version with one speed. Mechanical blade tensioning is achieved by means of a handwheel with stop screw, while the manual vice with quick lever locking system and knurled steel jaws ensures a secure clamping of the material, even when cutting tubes. The machine is fitted with blade guide blocks with bearings, a high-flow electric coolant pump for proper lubrication during cutting, and a blade cleaning brush to keep the blade clean and extend its service life. The ergonomically positioned control panel ensures easy and immediate operation. Working table height: 920 mm. Also available in HB version with gravity bow descent*.