

THOMAS 250 TECHNICS



						kW	rpm			OPTION	
		60	65	60	250x2.0x32	0.75/0.95	42/84	100 mm	95		
		60	65	60	 A= 530 mm B= 980 mm H= 775 mm IMBALLO / PACKING						  1PH kW 0,9
		50	55	50							
		60x45	90x45	60x45							
	35	40	35	 A= 805 mm B= 1050 mm INGOMBRO / DIMENSIONS							

Troncatrice a disco manuale 250 TECHNICS: pratica, sicura e maneggevole, indicata per il taglio di profili metallici e materiale pieno, adatta a lavorazioni di carpenteria leggera e lavori di manutenzione. Possibilità di taglio da **-45° a +45°**, da utilizzare con disco HSS con diametro massimo di **250 mm (alesaggio 32 mm)**. Disponibile con motore trifase a doppia velocità di taglio oppure monofase. Impugnatura con pulsante di comando ad azione mantenuta per avviare o arrestare il movimento del disco. **Morsa chiusura materiale manuale con sistema di bloccaggio rapido a leva completa di staffa anti-bava regolabile**, garantendo il doppio bloccaggio del pezzo. La ganaschia della morsa, regolabile assialmente, consente di serrare il pezzo il più vicino possibile alla linea di taglio. Dispositivo di lubrefrigerazione mediante pompa a membrana con rubinetto e filtro. Disponibile nella versione da banco o su piedistallo in lamiera d'acciaio. **Altezza piano di lavoro: 950 mm con piedistallo (optional).**

Manual circular saw 250 TECHNICS: practical, safe, and easy to handle, designed for cutting metal profiles and solid materials. Suitable for light fabrication work and maintenance tasks. Mitre cutting capability from **-45° to +45°**, to be used with an HSS blade with a maximum diameter of **250 mm (32 mm bore)**. Available with a three-phase motor with two cutting speeds or single-phase motor. Handle equipped with a hold-to-run control button to start and stop the blade rotation. **Manual material clamping vice with quick lever locking system, complete with adjustable anti-burr device**, ensuring double clamping of the workpiece. The vice jaw, adjustable axially, allows the workpiece to be clamped as close as possible to the cutting line. Coolant system with diaphragm pump, tap, and filter. Available in bench version or with steel sheet pedestal. **Working table height: 950 mm with pedestal (optional).**