



THOMAS 315 SUPER CUT



						kW	rpm			OPTION				
		45°	0°	45°	315x2.5x32	1.3/1.9	42/84	110 mm	125					
		90	95	90	 A= 630 mm B= 980 mm H= 895 mm IMBALLO / PACKING						 A= 900 mm B= 1120 mm INGOMBRO / DIMENSIONS		 PNEUMATIC	
		75	80	75										
		80x70	100x70	80x70										
		70	80	70	 rpm 22/44						 1PH kW 1,5			

Troncatrice a disco manuale 315 SUPER CUT: pratica, sicura e maneggevole, indicata per il taglio di profili metallici e materiale pieno, adatta a lavorazioni di carpenteria leggera e lavori di manutenzione. Possibilità di taglio da **-45° a +45°**, da utilizzare con disco HSS con diametro massimo di **315 mm (alesaggio 32 mm)**. Disponibile con motore trifase a doppia velocità di taglio oppure monofase. Impugnatura con pulsante di comando ad azione mantenuta per avviare o arrestare il movimento del disco. **Morsa chiusura materiale manuale con sistema di bloccaggio rapido a leva completa di staffa anti-bava regolabile**, garantendo il doppio bloccaggio del pezzo. La ganascia della morsa, regolabile assialmente, consente di serrare il pezzo il più vicino possibile alla linea di taglio. Dispositivo di lubrorefrigerazione mediante pompa a membrana con rubinetto e filtro. Disponibile nella versione da banco o su piedistallo in lamiera d'acciaio. **Altezza piano di lavoro: 990 mm con piedistallo (optional).**

Manual circular saw 315 SUPER CUT: practical, safe, and easy to handle, designed for cutting metal profiles and solid materials. Suitable for light fabrication work and maintenance tasks. Mitre cutting capability from **-45° to +45°**, to be used with an HSS blade with a maximum diameter of **315 mm (32 mm bore)**. Available with a three-phase motor with two cutting speeds or single-phase motor. Handle equipped with a hold-to-run control button to start and stop the blade rotation. **Manual material clamping vice with quick lever locking system, complete with adjustable anti-burr device**, ensuring double clamping of the workpiece. The vice jaw, adjustable axially, allows the workpiece to be clamped as close as possible to the cutting line. Coolant system with diaphragm pump, tap, and filter. Available in bench version or with steel sheet pedestal. **Working table height: 990 mm with pedestal (optional).**